

## **Enabling Voice Control of Voice-Controlled Apparatus**

### **Field of the Invention**

- 5 The present invention relates to the enabling of the voice control of voice-controlled apparatus.

### **Background of the Invention**

- 10 Voice control of apparatus is becoming more common and there are now well developed technologies for speech recognition particularly in contexts that only require small vocabularies.

- However, a problem exists where there are multiple voice-controlled apparatus in close proximity since their vocabularies are likely to overlap giving rise to the possibility of  
15 several different pieces of apparatus responding to the same voice command.

- It is known from US 5,991,726 to provide a proximity sensor on a piece of voice-controlled industrial machinery or equipment. Activation of the machinery or equipment by voice can only be effected if a person is standing nearby. However, pieces of industrial  
20 machinery or equipment of the type being considered are generally not closely packed so that whilst the proximity sensor has the effect of making voice control specific to the item concerned in that context, the same would not be true for voice controlled kitchen appliances as in the latter case the detection zones of the proximity sensors are likely to overlap.

- 25 One way of overcoming the problem of voice control activating multiple pieces of apparatus, is to require each voice command to be immediately preceded by speaking the name of the specific apparatus it is wished to control so that only that apparatus takes notice of the following command. This approach is not, however, user friendly and users  
30 frequently forget to follow such a command protocol, particularly when in a hurry.

It is an object of the present invention to provide a more user-friendly way of minimising the risk of unwanted activation of multiple voice-controlled apparatus by the same verbal command.

5

### **Summary of the Invention**

According to one aspect of the present invention, there is provided a method of enabling voice control of voice-controlled apparatus, involving:

- (a) detecting when the user is touching at least a predetermined portion of the apparatus;
- 10 (b) initially enabling the apparatus for voice control only when the user is detected in (a) as touching the apparatus.

According to another aspect of the present invention, there is provided apparatus with a voice-control user interface comprising:

- 15 - a speech recognition subsystem for recognising user voice commands for controlling the apparatus;
- a touch sensor for detecting when the user is touching at least a predetermined portion of the apparatus; and
- enablement control means for initially enabling the apparatus for voice control only if
- 20 the touch sensor detects that the user is touching the apparatus.

### **Brief Description of the Drawings**

A method and apparatus embodying the invention will now be described, by way of non-limiting example, with reference to the accompanying diagrammatic drawings, in which:

- 25 . **Figure 1** is a diagram illustrating a room equipped with three voice-controlled devices embodying the invention;
- . **Figure 2** is a diagram showing a Figure 1 device with a touch-sensitive zone along its front edge; and
- 30 . **Figure 3** is a diagram showing a Figure 1 device with a touch-sensitive fabric zone on its top surface.

### **Best Mode of Carrying Out the Invention**

Figure 1 shows a work space 11 in which a user 10 is present. Within the space 11 are three voice-controlled devices 14 (hereinafter referred to as devices A, B and C respectively) each with different functionality but each provided with a similar user interface subsystem permitting voice control of the device by the user.

More particularly, and with reference to device C, the user-interface subsystem comprises a microphone 15 feeding a speech recognition unit 17 adapted to recognise a small vocabulary of command words associated with the device, a touch sensor 16, and an activation control block 18. The output of the speech recognition unit is passed to a control block 20 for controlling the main functionality of the device itself (the control block can also receive input from other types of input controls such as mechanical switches so as to provide an alternative to the voice-controlled interface).

If the user 10 just speaks without touching touch sensor 16, the activation control block keeps the speech recogniser in an inhibited state and the latter therefore produces no output to the device control block. However, upon the user touching the sensor 16 the activation control block 18 enables the speech recognition unit to receive and interpret voice commands from the user. This initial enablement only exists whilst the sensor is touched, possibly extended for a short period (e.g. one second) after touching ceases. Only if the user speaks during this initial enablement phase does the activation control block 18 continue to enable the speech recognition unit 17 after the user stops touching sensor 16. For this purpose (and as indicated by dashed arrow 28 in Figure 1), the block 25 is fed with an output from the speech recognition unit 17 that simply indicates whether or not the user is speaking (here intended to encompass the whole range of sounds that humans can make). A delayed-disablement block 40 of control block 18 is activated if the output 28 indicates that the user is speaking during the initial enablement phase (that is, when the user is touching the sensor 16). The delayed-disablement block 40 when activated ensures that the speech recognition unit 17 continues to be enabled, after the user ceases touching the sensor 16, but only whilst the user continues speaking and for a limited further period timed by timer 41 (and, for example, of 10 seconds duration) in case the user wishes to

5

10

15

20

- 25

30

To encourage users to become used to touching the devices 14, the touch sensors can be given fabric/cloth covered active areas (see Figure 3) – in particular, a material with a pile that is pleasant to stroke can be used (and, indeed, activation of the sensor can be made

Many other variants are, of course, possible to the arrangement described above. For example, the activation control block could be arranged to enable the speech recognition unit only whilst the sensor 16 is being touched.

5